```
RRRRRRRRRRRR      TTTTTTTTTTTTTTT  PPPPPPPPPPPP        AAAAAAAAA     DDDDDDDDDDD
RRRRRRRRRRRR      TTTTTTTTTTTTTTT  PPPPPPPPPPPP        AAAAAAAAA     DDDDDDDDDDD
RRRRRRRRRRRR      TTTTTTTTTTTTTTT  PPPPPPPPPPPP        AAAAAAAAA     DDDDDDDDDDD
RRR          RRR        TTT        PPP          PPP   AAA         AAA   DDD         DDD
RRR          RRR        TTT        PPP          PPP   AAA         AAA   DDD         DDD
RRR          RRR        TTT        PPP          PPP   AAA         AAA   DDD         DDD
RRR          RRR        TTT        PPP          PPP   AAA         AAA   DDD         DDD
RRR          RRR        TTT        PPP          PPP   AAA         AAA   DDD         DDD
RRR          RRR        TTT        PPP          PPP   AAA         AAA   DDD         DDD
RRRRRRRRRRRR            TTT        PPPPPPPPPPPP       AAA         AAA   DDD         DDD
RRRRRRRRRRRR            TTT        PPPPPPPPPPPP       AAA         AAA   DDD         DDD
RRRRRRRRRRRR            TTT        PPPPPPPPPPPP       AAA         AAA   DDD         DDD
RRR    RRR              TTT        PPP                AAAAAAAAAAAAAAA   DDD         DDD
RRR    RRR              TTT        PPP                AAAAAAAAAAAAAAA   DDD         DDD
RRR    RRR              TTT        PPP                AAAAAAAAAAAAAAA   DDD         DDD
RRR       RRR           TTT        PPP                AAA         AAA   DDD         DDD
RRR       RRR           TTT        PPP                AAA         AAA   DDD         DDD
RRR       RRR           TTT        PPP                AAA         AAA   DDD         DDD
RRR          RRR        TTT        PPP                AAA         AAA   DDDDDDDDDDDD
RRR          RRR        TTT        PPP                AAA         AAA   DDDDDDDDDDDD
RRR          RRR        TTT        PPP                AAA         AAA   DDDDDDDDDDDD
```

FILEID**RTDEF

```
RRRRRRRR    TTTTTTTTTT  DDDDDDDD    EEEEEEEEEE  FFFFFFFFFF
RRRRRRRR    TTTTTTTTTT  DDDDDDDD    EEEEEEEEEE  FFFFFFFFFF
RR      RR      TT      DD      DD  EE          FF
RR      RR      TT      DD      DD  EE          FF
RR      RR      TT      DD      DD  EE          FF
RR      RR      TT      DD      DD  EE          FF
RRRRRRRR        TT      DD      DD  EEEEEEEE    FFFFFFFF
RRRRRRRR        TT      DD      DD  EEEEEEEE    FFFFFFFF
RR  RR          TT      DD      DD  EE          FF
RR  RR          TT      DD      DD  EE          FF
RR    RR        TT      DD      DD  EE          FF              ....
RR    RR        TT      DD      DD  EE          FF              ....
RR      RR      TT      DDDDDDDD    EEEEEEEEEE  FF              ....
RR      RR      TT      DDDDDDDD    EEEEEEEEEE  FF              ....

  SSSSSSSS  DDDDDDDD    LL
  SSSSSSSS  DDDDDDDD    LL
SS          DD      DD  LL
SS          DD      DD  LL
SS          DD      DD  LL
SS          DD      DD  LL
  SSSSSS    DD      DD  LL
  SSSSSS    DD      DD  LL
        SS  DD      DD  LL
        SS  DD      DD  LL
        SS  DD      DD  LL
        SS  DD      DD  LL
SSSSSSSS    DDDDDDDD    LLLLLLLLLL
SSSSSSSS    DDDDDDDD    LLLLLLLLLL
```

```
{       Version 'V04-000'
{
{****************************************************************************
{*                                                                          *
{*  COPYRIGHT (c) 1978, 1980, 1982, 1984 BY                                 *
{*  DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.                  *
{*  ALL RIGHTS RESERVED.                                                    *
{*                                                                          *
{*  THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED   *
{*  ONLY IN  ACCORDANCE WITH  THE  TERMS  OF  SUCH  LICENSE  AND WITH THE   *
{*  INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR  ANY  OTHER   *
{*  COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY   *
{*  OTHER PERSON.  NO TITLE TO AND OWNERSHIP OF  THE  SOFTWARE IS  HEREBY   *
{*  TRANSFERRED.                                                            *
{*                                                                          *
{*  THE INFORMATION IN THIS SOFTWARE IS  SUBJECT TO CHANGE WITHOUT NOTICE   *
{*  AND  SHOULD  NOT  BE  CONSTRUED AS  A COMMITMENT BY DIGITAL EQUIPMENT   *
{*  CORPORATION.                                                            *
{*                                                                          *
{*  DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE  OR  RELIABILITY OF ITS   *
{*  SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.                 *
{*                                                                          *
{*                                                                          *
{****************************************************************************
{
{       V03-004 JLV0351         Jake VanNoy             10-APR-1984
{               Add UNBIND constants.
{
{       V03-003 JLV0334         Jake VanNoy             28-FEB-1984
{               Add new constants.
{
{       V03-002 JLV0293         Jake VanNoy             28-JUL-1983
{               Added FLG$ symbols. Include $TSADEF. Add read
{               verify and upline broadcast symbols.
{
{       V03-001 MHB0091         Mark Bramhall           3-Mar-1983
{               Added constant MAXMSG.

MODULE  $RTPADDEF;

CONSTANT maxmsg EQUALS 1050;    { Maximum link data message size

    AGGREGATE AST_BLOCK STRUCTURE PREFIX AST$;

        STATE   LONGWORD;       /* AST ROUTINE (STATE)
        IOSB    QUADWORD;       /* IOSB
        OPCODE  WORD;           /* OPCODE (VMS RTT mode)
        OFFSET  WORD;           /* OFFSET (CTERM)
        BUFSIZ  WORD;           /* BUFFER SIZE (CTERM)
        ODATA   LONGWORD;       /* OUTPUT DATA BUFFER (CTERM)
        ITMLST  LONGWORD;       /* ADDRESS OF ITEM LIST FOR READ
    END;

    AGGREGATE CTERM_FLAGS STRUCTURE PREFIX FLG$;

        CTERM           bitfield mask;  /* cterm protocol is running
```

```
        CTRL_CY         bitfield mask;  /* flushing due to ^C or ^Y
        CTRL_O          bitfield mask;  /* Control O state
        LOGGING         bitfield mask;  /* Logging output
        VAXHOST         bitfield mask;  /* HOST is a VAX
        CTRLC           bitfield mask;  /* enable standard ^C
    END;

    /* FLAGS DEFINED IN "RTPAD$LOG"

    AGGREGATE RTLOG_DBGFLAGS STRUCTURE PREFIX RTLOG$;

        BANNER          bitfield mask;  /* protocol banner
        TRACE           bitfield mask;  /* enable tracing to RTPAD$TRACE

    END;
/*
/* Event Flags
/*
    CONSTANT (
        LINKEFN                         /* NET LINK
            ) EQUALS 1 INCREMENT 1 PREFIX RT$ TAG C;

END_MODULE;
```

```
MODULE  $RTEDEF;

    AGGREGATE RTE_BLOCK STRUCTURE PREFIX RTE$;

    CONSTANT buflen EQUALS 80 TAG "c";  { Maximum message size
    flink       ADDRESS;                /* forward link
    blink       ADDRESS;                /* backward link
    size        WORD unsigned;          /* size of structure
    spare1      WORD;                   /* spare byte
    iosb        QUADWORD unsigned;      /* IOSB
    buf         CHARACTER LENGTH 80;    /* must match buflen above
    CONSTANT    length EQUALS . TAG "c";
    END;

END_MODULE;
```

```
MODULE  $TSADEF;

CONSTANT (
        bind,                           { bind request
        unbind,                         { unbind request
        rebind,                         { rebind request
        accept,                         { bind accept
        entermode,                      { enter mode
        exitmode,                       { exit mode
        confirm,                        { confirm mode
        nomode,                         { no mode
        data,                           { data (cterm message)
        mode                            { mode message
         ) EQUALS 1 INCREMENT 1 PREFIX "PRO$" TAG "C";

AGGREGATE oob STRUCTURE PREFIX oob TAG "";

    len_exclude LONGWORD TAG "";        /* Lengths are not used
    exclude     LONGWORD TAG "";
    len_include LONGWORD TAG "";
    include     LONGWORD TAG "";
    len_abort   LONGWORD TAG "";
    abort       LONGWORD TAG "";
    discard     LONGWORD TAG "";        /* discard output mask
    echo        LONGWORD TAG "";        /* standard echo mask
    CONSTANT    len EQUALS . TAG "";
END;

/*
/* Unbind reason codes
/*

CONSTANT (
        badvers,                        { incompatible version
        noport,                         { no portal available
        user,                           { user requested unbind (logout)
        disconnect,                     { disconnect (setmode hangup)
        unused1,
        unused2,
        proterr                         { protocol error
         ) EQUALS 1 INCREMENT 1 PREFIX "unbind$" TAG "c";

AGGREGATE cterm STRUCTURE PREFIX ctp$ ; /* cterm packet

/* Up tu DATSIZE matches RTTDRIVER RBF header

    flink       LONGWORD;               /* forward link
    blink       LONGWORD;               /* backward link
    size        WORD;                   /* size of structure
    type        BYTE;                   /* DYN code (BUFIO)
    spare1      BYTE;                   /* spare byte
    msgdat      LONGWORD;               /* message address
    usrbfr      LONGWORD;               /* user buffer
    datsize     WORD;                   /* data size
    irp         LONGWORD;               /* address of associated IRP
    jib         LONGWORD;               /* address of associated JIB
```

```
    spare2      LONGWORD;               /* spare for RTPAD?
    spare3      LONGWORD;               /* spare for RTPAD?

    #header = .;

/* start of protocol message

    pro_msgtype BYTE;                   /* Protocol message type
    pro_fill    BYTE;                   /* Protocol fill

/* start of cterm data packet

    msgsize     WORD;                   /* length of first message
    #header2 = .;

    msgtype     BYTE;                   /* message type

        CONSTANT (
            init,                       { Initiate              (H <---> S)
            start_rd,                   { Start Read            (H  ---> S)
            read_data,                  { Read Data             (H <---  S)
            out_band,                   { Out-of-Band           (H <---  S)
            unread,                     { Unread                (H  ---> S)
            clr_input,                  { Clear Input           (H  ---> S)
            write,                      { Write                 (H  ---> S)
            write_com,                  { Write Completion      (H <---  S)
            dis_state,                  { Discard State         (H <---  S)
            read_char,                  { Read Characteristics  (H  ---> S)
            char,                       { Characteristics       (H <---> S)
            check_inp,                  { Check Input           (H  ---> S)
            inp_count,                  { Input Count           (H <---  S)
            inp_state,                  { Input State           (H <---  S)
            vmsqio,                     { VMS specific QIO      (H <---> S)
            vms_brdcst,                 { VMS spec broadcast    (H <---  S)
            vms_readvfy )               { VMS spec read verify  (H  ---> S)
        EQUALS T INCREMENT 1 TAG "c_mt";
/*
/* Remainder of block overlaid based on value of msgtype:
/*
    msgfields UNION;
```

```
/*
/* init message structure (H <---> S)
/*
    init STRUCTURE;
        in_flags        BYTE;                   /* no flags defined
        in_version      BYTE;                   /* protocol version number
        in_eco          BYTE;                   /* ECO number for protocol
        in_mod          BYTE;                   /* customer modification number
        in_revision     CHARACTER LENGTH 8;     /* software revision number
        in_parmtype     BYTE;                   /* purpose of the following value
        in_parmval      BYTE;                   /* byte count

        CONSTANT len    EQUALS . TAG "c_in";        /* length of structure
        CONSTANT msglen EQUALS .-#header TAG "c_in";/* length of structure minus header
        CONSTANT prolen EQUALS .-#header2 TAG "c_in";/* length of structure minus header

    END init;
```

```
/*
/* start read and read verify structure (H ---> S)
/*
    start_rd STRUCTURE;
        sr_flags_overlay union fill;    /* Flags for unread
          sr_flags character length 3 TAG "L";  /* 3 bytes of flags
          sr_flag_bits structure fill;
            sr_underflo BITFIELD LENGTH 2;      /* - underflow handling
                CONSTANT (
                    ignore,                     { -- ignore underflow
                    bel,                        { -- ring bell on underflow
                    terminate )                 { -- terminate on underflow
                EQUALS 0 INCREMENT 1 TAG "m_sr";
            sr_purge    BITFIELD MASK;          /* - purge type ahead
            sr_format   BITFIELD MASK;          /* - formatting flag
            sr_trmvert  BITFIELD MASK;          /* - terminate on vertical
            sr_continue BITFIELD MASK;          /* - continuation read
            #shift = ^;
            sr_cvtlow   BITFIELD LENGTH 2;      /* - raise input
                CONSTANT (
                    no_cvt,                     { -- use upper/lower characteristic
                    none_only,                  { -- none this read only
                    lowtoup )                   { -- Normal lower to upper
                EQUALS 0 INCREMENT 1 TAG "c_sr";
                CONSTANT no_cvt    EQUALS ctp$c_sr_no_cvt@#shift TAG "m_sr";
                CONSTANT none_only EQUALS ctp$c_sr_none_only@#shift TAG "m_sr";
                CONSTANT lowtoup   EQUALS ctp$c_sr_lowtoup@#shift TAG "m_sr";
            #shift = ^;
            sr_control  BITFIELD LENGTH 3;      /* - disable control
                CONSTANT (
                    no_ctrl,                    { -- no control characters disabled
                    u_and_r,                    { -- ^U and ^R disabled
                    edit,                       { -- all edit control characters
                    allbutx,                    { -- all but XON/XOFF
                    all )                       { -- all
                EQUALS 0 INCREMENT 1 TAG "c_sr";
                CONSTANT no_ctrl EQUALS ctp$c_sr_no_ctrl@#shift TAG "m_sr";
                CONSTANT u_and_r EQUALS ctp$c_sr_u_and_r@#shift TAG "m_sr";
                CONSTANT edit    EQUALS ctp$c_sr_edit@#shift    TAG "m_sr";
                CONSTANT allbutx EQUALS ctp$c_sr_allbutx@#shift TAG "m_sr";
                CONSTANT all     EQUALS ctp$c_sr_all@#shift     TAG "m_sr";
            sr_noecho   BITFIELD MASK;          /* - no echo read
            sr_trmecho BITFIELD MASK;           /* - terminator echo
            sr_timed    BITFIELD MASK;          /* - read timeout
            #shift = ^;
            sr_term_set BITFIELD LENGTH 2;      /* - termination set
                CONSTANT (
                    prevterm,                   { -- use previous read terminators
                    thisterm,                   { -- use this read terminators
                    normterm )                  { -- use normal terminators
                EQUALS 0 INCREMENT 1 TAG "c_sr";
                CONSTANT prevterm EQUALS ctp$c_sr_prevterm@#shift TAG "m_sr";
                CONSTANT thisterm EQUALS ctp$c_sr_thisterm@#shift TAG "m_sr";
                CONSTANT normterm EQUALS ctp$c_sr_normterm@#shift TAG "m_sr";
            sr_noescape  BITFIELD MASK;         /* - don't recognize escape
            sr_escape    BITFIELD MASK;         /* - recognize escape
```

```
        /* VMS specific bits follow

        sr_noedit    BITFIELD MASK;          /* - disable editing
        sr_norecall  BITFIELD MASK;          /* - disable recall

      end sr_flag_bits;
    end sr_flags_overlay;

    sr_max_len      WORD;                    /* max length of read
    sr_end_data     WORD;                    /* end of data in read buffer
    sr_timeout      WORD;                    /* timeout value
    sr_end_prmt     WORD;                    /* end of prompt
    sr_str_disp     WORD;                    /* start of display
    sr_lo_water     WORD;                    /* low water mark

    TWO_READS structure;
        TWO_READS_OVERLAY union fill;

            sr_term         CHARACTER LENGTH 1;     /* termination set (byte counted field)

            /* read data starting position (after term set)

            CONSTANT len    EQUALS . TAG "c_sr";          /* length of structure
            CONSTANT msglen EQUALS .-#header TAG "c_sr";/* length of structure minus header
            CONSTANT prolen EQUALS .-#header2 TAG "c_sr";/* length of structure minus header

        READ_VERIFY structure ;

            sr2_altechsize  WORD UNSIGNED;          /* alt echo size
            sr2_picstrsize  WORD UNSIGNED;          /* picture string size
            sr2_editflags   WORD UNSIGNED;          /* flags
            sr2_fillchar    WORD UNSIGNED;          /* fill characters
            sr2_term        CHARACTER LENGTH 1;     /* terminator set

            CONSTANT len    EQUALS . TAG "c_sr2";         /* length of structure
            CONSTANT msglen EQUALS .-#header TAG "c_sr2";  /* length of structure minus header
            CONSTANT prolen EQUALS .-#header2 TAG "c_sr2"; /* length of structure minus header
        end READ_VERIFY;
        end TWO_READS_OVERLAY;
    end TWO_READS;

END start_rd;
```

```
/*
/* read data structure (H <--- S)
/*
    read_data STRUCTURE;
        rd_flags_overlay union fill;    /* Flags for unread
          rd_flags_byte unsigned;
          rd_flag_bits structure fill;
            rd_com_code BITFIELD LENGTH 4;      /* - completion code
                CONSTANT (
                    normal,                     ( -- normal terminator
                    valesc,                     ( -- valid escape
                    invesc,                     ( -- invalid escape
                    outband,                    ( -- out of band
                    inpfull,                    ( -- input buffer full
                    timeout,                    ( -- read timed out
                    unread,                     ( -- unread request received
                    underflo,                   ( -- underflow
                    abstoken,                   ( -- absentee token
                    vert_cng,                   ( -- veritcal postition change
                    linebrk,                    ( -- line break
                    framerr,                    ( -- frame error
                    parity,                     ( -- parity error
                    overun )                    ( -- receiver over-run
                EQUALS 0 INCREMENT 1 TAG "m_rd";
            rd_mor_data BITFIELD MASK;          /* - more data in typeahead
          end rd_flag_bits;
        end rd_flags_overlay;
        rd_lo_water     WORD;                   /* low water
        rd_vert_cng     BYTE;                   /* vertical change since read started
        rd_curs_pos     BYTE;                   /* cursor position from EOL
        rd_term_pos     WORD;                   /* position of terminator
        rd_data         CHARACTER LENGTH 0;     /* start of read data

        CONSTANT len    EQUALS . TAG "c_rd";        /* length of structure
        CONSTANT msglen EQUALS .-#header TAG "c_rd"; /* length of structure minus header
        CONSTANT prolen EQUALS .-#header2 TAG "c_rd"; /* length of structure minus header

END read_data;
```

```
/*
/* out of band structure (H <--- S)
/*
    out_band STRUCTURE;

        ob_flags_overlay union fill;    /* Flags for unread
          ob_flags byte unsigned;
          ob_flag_bits structure fill;
            ob_linebrk  BITFIELD MASK;          /* - line break occured
          end ob_flag_bits;
        end ob_flags_overlay;

        ob_char         BYTE;                   /* one byte of data

        CONSTANT len    EQUALS . TAG "c_ob";        /* length of structure
        CONSTANT msglen EQUALS .-#header TAG "c_ob"; /* length of structure minus header
        CONSTANT prolen EQUALS .-#header2 TAG "c_ob"; /* length of structure minus header

    END out_band;
```

```
/*
/*  unread structure (H ---> S)
/*
    unread STRUCTURE;

        ur_flags_overlay union fill;    /* Flags for unread
          ur_flags_byte unsigned;
          ur_flag_bits structure fill;
            ur_cond     BITFIELD MASK;          /* - unread conditional
          end ur_flag_bits;
        end ur_flags_overlay;

        CONSTANT len    EQUALS . TAG "c_ur";        /* length of structure
        CONSTANT msglen EQUALS .-#header TAG "c_ur"; /* length of structure minus header
        CONSTANT prolen EQUALS .-#header2 TAG "c_ur"; /* length of structure minus header

    END unread;
```

```
/*
/* clear input structure (H ---> S)
/*
    clr_input STRUCTURE;
        ci_flags        BYTE;                       /* no flags defined

        CONSTANT len    EQUALS . TAG "c_ci";        /* length of structure
        CONSTANT msglen EQUALS .-#header TAG "c_ci"; /* length of structure minus header
        CONSTANT prolen EQUALS .-#header2 TAG "c_ci"; /* length of structure minus header

    END clr_input;
```

```
/*
/* write structure (H ---> S)
/*
    write STRUCTURE;
        wr_flags_overlay union fill;    /* Flags for write
          wr_flags_word unsigned;
          wr_flag_bits structure fill;
            wr_lock     BITFIELD LENGTH 2;      /* - locking
                CONSTANT (
                    noaction,                   { -- no locking action
                    before,                     { -- lock before, leave locked
                    befaft,                     { -- lock before, unlock after
                    befaftre )                  { -- lock before, unlock after, redisplay
                EQUALS 0 INCREMENT 1 TAG "m_wr";
            wr_newline  BITFIELD MASK;          /* - VMS specific, newline modifier
            wr_discard  BITFIELD MASK;          /* - cancel ^O
            wr_begin    BITFIELD MASK;          /* - beginning of write
            wr_end      BITFIELD MASK;          /* - end of write
            #shift = ^;
            wr_prefix   BITFIELD LENGTH 2;      /* - prefix code
                CONSTANT (
                    no_fix,                     { -- no prefix
                    newlinecnt,                 { -- new line count
                    char )                      { -- character prefix
                EQUALS 0 INCREMENT 1 TAG "c_wr";
                CONSTANT no_fix  EQUALS ctp$c_wr_no_fix@#shift  TAG "m_wr";
                CONSTANT newlinecnt EQUALS ctp$c_wr_newlinecnt@#shift TAG "m_wr";
                CONSTANT char    EQUALS ctp$c_wr_char@#shift    TAG "m_wr";
            wr_postfix  BITFIELD LENGTH 2;      /* - postfix code
            wr_status   BITFIELD MASK;          /* - return status
            wr_transparent BITFIELD MASK;       /* - write passall
          END wr_flag_bits;
        END wr_flags_overlay;
        wr_prefix       BYTE;                   /* prefix value
        wr_postfix      BYTE;                   /* postfix value
        wr_data         CHARACTER LENGTH 0;     /* start of data

        CONSTANT len    EQUALS . TAG "c_wr";        /* length of structure
        CONSTANT msglen EQUALS .-#header TAG "c_wr"; /* length of structure minus header
        CONSTANT prolen EQUALS .-#header2 TAG "c_wr"; /* length of structure minus header

END write;
```

```
/*
/* write completion structure (H <--- S)
/*
    write_com STRUCTURE;
        wc_flags_overlay union fill;    /* Flags for unread
          wc_flags byte unsigned;
          wc_flag_bits structure fill;
            wc_discard  BITFIELD MASK;          /* - discard state
          end wc_flag_bits;
        end wc_flags_overlay;

        wc_horpos       WORD;                   /* horizontal position
        wc_verpos       WORD;                   /* vertical position

        CONSTANT len    EQUALS . TAG "c_wc";        /* length of structure
        CONSTANT msglen EQUALS .-#header TAG "c_wc"; /* length of structure minus header
        CONSTANT prolen EQUALS .-#header2 TAG "c_wc"; /  length of structure minus header

    END write_com;
```

```
/*
/* discard state structure (H <--- S)
/*
    dis_state STRUCTURE;
        ds_flags_overlay union fill;    /* Flags for unread
          ds_flags byte unsigned;
          ds_flag_bits structure fill;
            ds_discard  BITFIELD MASK;          /* - discard state
          end ur_flag_bits;
        end ur_flags_overlay;

        CONSTANT len    EQUALS . TAG "c_ds";          /* length of structure
        CONSTANT msglen EQUALS .-#header TAG "c_ds"; /* length of structure minus header
        CONSTANT prolen EQUALS .-#header2 TAG "c_ds"; /* length of structure minus header

    END dis_state;
```

```
/*
/* read characteristics structure (H ---> S)
/*
    read_char STRUCTURE;
        rc_flags        BYTE;                   /* no flags defined
        rc_selector     WORD;                   /* selector start position

        CONSTANT len    EQUALS . TAG "c_rc";          /* length of structure
        CONSTANT msglen EQUALS .-#header TAG "c_rc"; /* length of structure minus header
        CONSTANT prolen EQUALS .-#header2 TAG "c_rc"; /* length of structure minus header

    END read_char;
```

```
/*
/* characteristics structure (H <---> S)
/*
    char STRUCTURE;
        ch_flags        BYTE;                       /* no flags defined
        ch_param        WORD;                       /* start of characteristics
        ch_value        CHARACTER LENGTH 0;         /* value

        CONSTANT len    EQUALS . TAG "c_ch";            /* length of structure
        CONSTANT msglen EQUALS .-#header TAG "c_ch"; /* length of structure minus header
        CONSTANT prolen EQUALS .-#header2 TAG "c_ch"; /* length of structure minus header

        /* characteristics selector types

        CONSTANT (
                physical,
                logical,
                cterm
                ) EQUALS 0 INCREMENT 1 PREFIX "CHS" TAG C;

        /* characteristics selectors, type = physical

        CONSTANT (
                in_speed,
                out_speed,
                char_size,
                parity_enable,
                parity_type,
                modem_present,
                autobaud,
                manage_guar,
                swchar1,
                swchar2,
                eightbit,
                manage_ena
                ) EQUALS 1 INCREMENT 1 PREFIX "CHS" TAG "C_PH";

    /* characteristics selectors, type = logical

    CONSTANT (
            mode_writing,
            term_bits,
            term_type,
            output_flow,
            page_stop,
            flow_char_pass,
            input_flow,
            loss_notif,
            line_width,
            page_length,
            stop_length,
            cr_fill,
            lf_fill,
            wrap,
            hor_tab,
            vert_tab,
```

```
            form_feed
            ) EQUALS 1 INCREMENT 1 PREFIX "CH$" TAG "C_LG";

    /* characteristics selectors, type = cterm

    CONSTANT (
            ignore_input,
            char_att,                   /* see tty_attributes, etc. below
            ctrlo_pass,
            raise_input,
            normal_echo,
            input_esc,
            output_esc,
            input_count,
            auto_prompt,
            error_processing
            ) EQUALS 1 INCREMENT 1 PREFIX "CH$" TAG "C_CT";

    CONSTANT (
            even,
            odd,
            clear,          /* no support for set or clear on VMS
            set
            ) EQUALS 1 INCREMENT 1 PREFIX "CH$" TAG C_PARITY;

    tty_attributes STRUCTURE;
        ch_known    BITFIELD MASK;
        ch_scope    BITFIELD MASK;
    end tty_attributes;

    oob_handling STRUCTURE;
        ch_oo       bitfield mask length 2; /* out of band handling
        ch_i        bitfield mask;          /* include character
        ch_d        bitfield mask;          /* discard output
        ch_ee       bitfield mask length 2; /* echo control
        ch_f        bitfield mask;          /* special enable
    end oob_handling;

    oob_data STRUCTURE;
        ch_char     BYTE;           /* data character
        ch_mask     BYTE;           /* mask for attributes
        ch_attr     BYTE;           /* attributes
    end oob_data;

    CONSTANT (                      { - out of band flags
        cancel,                     { -- cancel previous    0
        iclear,                     { -- immediate clear    1
        dclear,                     { -- deferred clear     2
        hello )                     { -- hello              3
    EQUALS 0 INCREMENT 1 TAG "c_ch";

    CONSTANT (                      { echo control
        echonone,                   { -- don't echo
        echoself,                   { -- echo character as self
        echostandard,               { -- standard echo
```

```
        echoboth )                          { -- echo both
      EQUALS 0 INCREMENT 1 TAG "c_ch";

   END char;
```

```
/*
/* check input structure (H ---> S)
/*
    check_inp STRUCTURE;
        ck_flags        BYTE;                   /* no flags defined

        CONSTANT len    EQUALS . TAG "c_ck";        /* length of structure
        CONSTANT msglen EQUALS .-#header TAG "c_ck"; /* length of structure minus header
        CONSTANT prolen EQUALS .-#header2 TAG "c_ck"; /* length of structure minus heade

    END check_inp;
```

```
/*
/* input count structure (H <--- S)
/*
    inp_count STRUCTURE;
        ic_flags        BYTE;                   /* no flags defined
        ic_count        WORD;                   /* input count

        CONSTANT len    EQUALS . TAG "c_ic";        /* length of structure
        CONSTANT msglen EQUALS .-#header TAG "c_ic"; /* length of structure minus header
        CONSTANT prolen EQUALS .-#header2 TAG "c_ic"; /* length of structure minus header

    END inp_count;
```

```
/*
/* input state structure (H <--- S)
/*
    inp_state STRUCTURE;
        is_flags_overlay union fill;    /* Flags for unread
          ts_flags byte unsigned;
          is_flag_bits structure fill;
            ts_nonzero  BITFIELD MASK;          /* - count change to non-zero
          end ts_flag_bits;
        end is_flags_overlay;

        CONSTANT len    EQUALS . TAG "c_is";        /* length of structure
        CONSTANT msglen EQUALS .-#header TAG "c_is"; /* length of structure minus header
        CONSTANT prolen EQUALS .-#header2 TAG "c_is"; /* length of structure minus header

    END inp_state;

/*
/* VMS QIO REQUEST (H ---> S)
/*
    vmsqio STRUCTURE;
        vms_flags_overlay union fill;   /* Flags for unread
          vms_flags byte unsigned;
          vms_flag_bits structure fill;
            vms_useiosb BITFIELD MASK;          /* use iosb to determine length
            vms_readlen BITFIELD MASK;          /* - read-type iosb buffer length
          end vms_flag_bits;
        end vms_flags_overlay;

        vms_reqid       LONGWORD;               /* qio request id

        vmsfields UNION;

            VMSREQ STRUCTURE;                   /* request
                vms_func        WORD;                   /* qio function code
                vms_plen        WORD;                   /* these four are repeated...
                vms_pcode       WORD;                   /*   for each parameter
                vms_pflags      STRUCTURE TAG W;        /*
                    vms_ref     BITFIELD MASK;          /* - pass by reference
                    vms_item    BITFIELD MASK;          /* - item list or Pn
                    vms_buffer  BITFIELD MASK;          /* - this is return buffer
                    vms_fill2   BITFIELD LENGTH 16-^;   /* - fill to 1 word
                    END vms_pflags;
                vms_pdata       CHARACTER LENGTH 0;     /* value

                CONSTANT len    EQUALS . TAG "c_vms";       /* length of structure
                CONSTANT msglen EQUALS .-#header TAG "c_vms"; /* length of structure minus header
                CONSTANT prolen EQUALS .-#header2 TAG "c_vms"; /* length of structure minus header
            END VMSREQ;

            VMSRESP STRUCTURE;
                vms_iosb        QUADWORD;               /* iosb
                vms_rdata       CHARACTER LENGTH 0;     /* start of data
            END VMSRESP;

        END vmsfields;
```

```
    END vmsqio;
```

```
/*
/* upline broadcast (H <--- S)
/*
    broadcast STRUCTURE;
        br_flags        WORD UNSIGNED;          /* no flags defined
        br_msgcode      WORD UNSIGNED;          /* mailbox message code
        br_unitnum      WORD UNSIGNED;          /* unit number
        br_devname      CHARACTER LENGTH 16;    /* device name
        br_msglen       WORD UNSIGNED;          /* length of text
        br_msgtxt       CHARACTER LENGTH 0;     /* start of text

        CONSTANT len    EQUALS . TAG "c_br";        /* length of structure
        CONSTANT msglen EQUALS .-#header TAG "c_br"; /* length of structure minus header
        CONSTANT prolen EQUALS .-#header2 TAG "c_br"; /* length of structure minus header

    END broadcast;

END msgfields; /* end of protocol messages

END cterm;
```

```
AGGREGATE VMSQIO STRUCTURE PREFIX vms$;

        plen    WORD;                   /* these four are repeated...
        pflags  WORD;                   /*   ...
        pcode   WORD;                   /*   ... for each parameter
        pdata   CHARACTER LENGTH 0;     /* value

END; /* VMSQIO

END_MODULE;
```

RPGMSGTXT
LIS

DTE_DF03
MAP

RPGMOVE3
LIS

RPGSORT
LIS

RPGOPEN
LIS

RTPAD

CTDRIVER
MAP

RTPAD
MAP

RTPADMACS
MAR

RPGMSGPTR
LIS

RPGVECTOR
LIS

RPGPRINT
LIS

RPGUDATE
LIS

RTDEF
SDL

DTE_DF03
MAR

CTDRIVER
LIS